geojson Documentation

Release latest

May 28, 2023

Contents

1 Installation **3**

2 GeoJSON Objects **5**
- 2.1 Point . . . 5
- 2.2 MultiPoint . . . 5
- 2.3 LineString . . . 6
- 2.4 MultiLineString . . . 6
- 2.5 Polygon . . . 6
- 2.6 MultiPolygon . . . 6
- 2.7 GeometryCollection . . . 7
- 2.8 Feature . . . 7
- 2.9 FeatureCollection . . . 8

3 GeoJSON encoding/decoding **9**
- 3.1 Custom classes . . . 9
- 3.2 Default and custom precision . . . 10

4 Helpful utilities **11**
- 4.1 coords . . . 11
- 4.2 map_coords . . . 11
- 4.3 map_tuples . . . 12
- 4.4 map_geometries . . . 12
- 4.5 validation . . . 12
- 4.6 generate_random . . . 12

5 Development **15**

6 Credits **17**

This Python library contains:

- Functions for encoding and decoding GeoJSON formatted data
- Classes for all GeoJSON Objects
- An implementation of the Python __geo_interface__ Specification

Table of Contents

- *Installation*
- *GeoJSON Objects*
  - *Point*
  - *MultiPoint*
  - *LineString*
  - *MultiLineString*
  - *Polygon*
  - *MultiPolygon*
  - *GeometryCollection*
  - *Feature*
  - *FeatureCollection*
- *GeoJSON encoding/decoding*
  - *Custom classes*
  - *Default and custom precision*
- *Helpful utilities*
  - *coords*
  - *map_coords*
  - *map_tuples*
  - *map_geometries*
  - *validation*
  - *generate_random*
- *Development*
- *Credits*

CHAPTER 1

Installation

geojson is compatible with Python 3.7 - 3.11. The recommended way to install is via pip:

```
pip install geojson
```

CHAPTER 2

GeoJSON Objects

This library implements all the GeoJSON Objects described in The GeoJSON Format Specification.

All object keys can also be used as attributes.

The objects contained in GeometryCollection and FeatureCollection can be indexed directly.

2.1 Point

```
>>> from geojson import Point

>>> Point((-115.81, 37.24))
{"coordinates": [-115.8..., 37.2...], "type": "Point"}
```

Visualize the result of the example above here. General information about Point can be found in Section 3.1.2 and Appendix A: Points within The GeoJSON Format Specification.

2.2 MultiPoint

```
>>> from geojson import MultiPoint

>>> MultiPoint([(-155.52, 19.61), (-156.22, 20.74), (-157.97, 21.46)])
{"coordinates": [[-155.5..., 19.6...], [-156.2..., 20.7...], [-157.9..., 21.4...]],
↪"type": "MultiPoint"}
```

Visualize the result of the example above here. General information about MultiPoint can be found in Section 3.1.3 and Appendix A: MultiPoints within The GeoJSON Format Specification.

2.3 LineString

```
>>> from geojson import LineString

>>> LineString([(8.919, 44.4074), (8.923, 44.4075)])
{"coordinates": [[8.91..., 44.407...], [8.92..., 44.407...]], "type": "LineString"}
```

Visualize the result of the example above here. General information about LineString can be found in Section 3.1.4 and Appendix A: LineStrings within The GeoJSON Format Specification.

2.4 MultiLineString

```
>>> from geojson import MultiLineString

>>> MultiLineString([
...     [(3.75, 9.25), (-130.95, 1.52)],
...     [(23.15, -34.25), (-1.35, -4.65), (3.45, 77.95)]
... ])
{"coordinates": [[[3.7..., 9.2...], [-130.9..., 1.52...]], [[23.1..., -34.2...], [-1.
↪3..., -4.6...], [3.4..., 77.9...]]], "type": "MultiLineString"}
```

Visualize the result of the example above here. General information about MultiLineString can be found in Section 3.1.5 and Appendix A: MultiLineStrings within The GeoJSON Format Specification.

2.5 Polygon

```
>>> from geojson import Polygon

>>> # no hole within polygon
>>> Polygon([[(2.38, 57.322), (-120.43, 19.15), (23.194, -20.28), (2.38, 57.322)]])
{"coordinates": [[[2.3..., 57.32...], [-120.4..., 19.1...], [23.19..., -20.2...]]],
↪"type": "Polygon"}

>>> # hole within polygon
>>> Polygon([
...     [(2.38, 57.322), (-120.43, 19.15), (23.194, -20.28), (2.38, 57.322)],
...     [(-5.21, 23.51), (15.21, -10.81), (-20.51, 1.51), (-5.21, 23.51)]
... ])
{"coordinates": [[[2.3..., 57.32...], [-120.4..., 19.1...], [23.19..., -20.2...]], [[-
↪5.2..., 23.5...], [15.2..., -10.8...], [-20.5..., 1.5...], [-5.2..., 23.5...]]],
↪"type": "Polygon"}
```

Visualize the results of the example above here. General information about Polygon can be found in Section 3.1.6 and Appendix A: Polygons within The GeoJSON Format Specification.

2.6 MultiPolygon

```
>>> from geojson import MultiPolygon
```

(continues on next page)

(continued from previous page)

```
>>> MultiPolygon([
...     ([(3.78, 9.28), (-130.91, 1.52), (35.12, 72.234), (3.78, 9.28)],),
...     ([(23.18, -34.29), (-1.31, -4.61), (3.41, 77.91), (23.18, -34.29)],)
... ])
{"coordinates": [[[[3.7..., 9.2...], [-130.9..., 1.5...], [35.1..., 72.23...]]],␣
↪[[[23.1..., -34.2...], [-1.3..., -4.6...], [3.4..., 77.9...]]]], "type":
↪"MultiPolygon"}
```

Visualize the result of the example above here. General information about MultiPolygon can be found in Section 3.1.7 and Appendix A: MultiPolygons within The GeoJSON Format Specification.

2.7 GeometryCollection

```
>>> from geojson import GeometryCollection, Point, LineString

>>> my_point = Point((23.532, -63.12))

>>> my_line = LineString([(-152.62, 51.21), (5.21, 10.69)])

>>> geo_collection = GeometryCollection([my_point, my_line])

>>> geo_collection
{"geometries": [{"coordinates": [23.53..., -63.1...], "type": "Point"}, {"coordinates
↪": [[-152.6..., 51.2...], [5.2..., 10.6...]], "type": "LineString"}], "type":
↪"GeometryCollection"}

>>> geo_collection[1]
{"coordinates": [[-152.62, 51.21], [5.21, 10.69]], "type": "LineString"}

>>> geo_collection[0] == geo_collection.geometries[0]
True
```

Visualize the result of the example above here. General information about GeometryCollection can be found in Section 3.1.8 and Appendix A: GeometryCollections within The GeoJSON Format Specification.

2.8 Feature

```
>>> from geojson import Feature, Point

>>> my_point = Point((-3.68, 40.41))

>>> Feature(geometry=my_point)
{"geometry": {"coordinates": [-3.68..., 40.4...], "type": "Point"}, "properties": {},
↪"type": "Feature"}

>>> Feature(geometry=my_point, properties={"country": "Spain"})
{"geometry": {"coordinates": [-3.68..., 40.4...], "type": "Point"}, "properties": {
↪"country": "Spain"}, "type": "Feature"}

>>> Feature(geometry=my_point, id=27)
{"geometry": {"coordinates": [-3.68..., 40.4...], "type": "Point"}, "id": 27,
↪"properties": {}, "type": "Feature"}
```

Visualize the results of the examples above here. General information about Feature can be found in Section 3.2 within The GeoJSON Format Specification.

2.9 FeatureCollection

```
>>> from geojson import Feature, Point, FeatureCollection

>>> my_feature = Feature(geometry=Point((1.6432, -19.123)))

>>> my_other_feature = Feature(geometry=Point((-80.234, -22.532)))

>>> feature_collection = FeatureCollection([my_feature, my_other_feature])

>>> feature_collection
{"features": [{"geometry": {"coordinates": [1.643..., -19.12...], "type": "Point"},
↪"properties": {}, "type": "Feature"}, {"geometry": {"coordinates": [-80.23..., -22.
↪53...], "type": "Point"}, "properties": {}, "type": "Feature"}], "type":
↪"FeatureCollection"}

>>> feature_collection.errors()
[]

>>> (feature_collection[0] == feature_collection['features'][0], feature_
↪collection[1] == my_other_feature)
(True, True)
```

Visualize the result of the example above here. General information about FeatureCollection can be found in Section 3.3 within The GeoJSON Format Specification.

CHAPTER 3

GeoJSON encoding/decoding

All of the GeoJSON Objects implemented in this library can be encoded and decoded into raw GeoJSON with the `geojson.dump`, `geojson.dumps`, `geojson.load`, and `geojson.loads` functions. Note that each of these functions is a wrapper around the core *json* function with the same name, and will pass through any additional arguments. This allows you to control the JSON formatting or parsing behavior with the underlying core *json* functions.

```
>>> import geojson

>>> my_point = geojson.Point((43.24, -1.532))

>>> my_point
{"coordinates": [43.2..., -1.53...], "type": "Point"}

>>> dump = geojson.dumps(my_point, sort_keys=True)

>>> dump
'{"coordinates": [43.2..., -1.53...], "type": "Point"}'

>>> geojson.loads(dump)
{"coordinates": [43.2..., -1.53...], "type": "Point"}
```

3.1 Custom classes

This encoding/decoding functionality shown in the previous can be extended to custom classes using the interface described by the __geo_interface__ Specification.

```
>>> import geojson

>>> class MyPoint():
...     def __init__(self, x, y):
...         self.x = x
...         self.y = y
```

(continues on next page)

(continued from previous page)

```
...
...     @property
...     def __geo_interface__(self):
...         return {'type': 'Point', 'coordinates': (self.x, self.y)}

>>> point_instance = MyPoint(52.235, -19.234)

>>> geojson.dumps(point_instance, sort_keys=True)
'{"coordinates": [52.23..., -19.23...], "type": "Point"}'
```

3.2 Default and custom precision

GeoJSON Object-based classes in this package have an additional *precision* attribute which rounds off coordinates to 6 decimal places (roughly 0.1 meters) by default and can be customized per object instance.

```
>>> from geojson import Point

>>> Point((-115.123412341234, 37.123412341234))  # rounded to 6 decimal places by␣
↪default
{"coordinates": [-115.123412, 37.123412], "type": "Point"}

>>> Point((-115.12341234, 37.12341234), precision=8)  # rounded to 8 decimal places
{"coordinates": [-115.12341234, 37.12341234], "type": "Point"}
```

Precision can be set at the package level by setting *geojson.geometry.DEFAULT_PRECISION*

```
>>> import geojson

>>> geojson.geometry.DEFAULT_PRECISION = 5

>>> from geojson import Point

>>> Point((-115.12341234, 37.12341234))  # rounded to 8 decimal places
{"coordinates": [-115.12341, 37.12341], "type": "Point"}
```

After setting the DEFAULT_PRECISION, coordinates will be rounded off to that precision with *geojson.load* or *geojson.loads*. Following one of those with *geojson.dump* is a quick and easy way to scale down the precision of excessively precise, arbitrarily-sized GeoJSON data.

CHAPTER 4

Helpful utilities

4.1 coords

`geojson.utils.coords` yields all coordinate tuples from a geometry or feature object.

```
>>> import geojson

>>> my_line = LineString([(-152.62, 51.21), (5.21, 10.69)])

>>> my_feature = geojson.Feature(geometry=my_line)

>>> list(geojson.utils.coords(my_feature))
[(-152.62..., 51.21...), (5.21..., 10.69...)]
```

4.2 map_coords

`geojson.utils.map_coords` maps a function over all coordinate values and returns a geometry of the same type. Useful for scaling a geometry.

```
>>> import geojson

>>> new_point = geojson.utils.map_coords(lambda x: x/2, geojson.Point((-115.81, 37.
↪24)))

>>> geojson.dumps(new_point, sort_keys=True)
'{"coordinates": [-57.905..., 18.62...], "type": "Point"}'
```

4.3 map_tuples

`geojson.utils.map_tuples` maps a function over all coordinates and returns a geometry of the same type. Useful for changing coordinate order or applying coordinate transforms.

```
>>> import geojson

>>> new_point = geojson.utils.map_tuples(lambda c: (c[1], c[0]), geojson.Point((-115.
↪81, 37.24)))

>>> geojson.dumps(new_point, sort_keys=True)
'{"coordinates": [37.24..., -115.81], "type": "Point"}'
```

4.4 map_geometries

`geojson.utils.map_geometries` maps a function over each geometry in the input.

```
>>> import geojson

>>> new_point = geojson.utils.map_geometries(lambda g: geojson.MultiPoint([g[
↪"coordinates"]]), geojson.GeometryCollection([geojson.Point((-115.81, 37.24))]))

>>> geojson.dumps(new_point, sort_keys=True)
'{"geometries": [{"coordinates": [[-115.81, 37.24]], "type": "MultiPoint"}], "type":
↪"GeometryCollection"}'
```

4.5 validation

`is_valid` property provides simple validation of GeoJSON objects.

```
>>> import geojson

>>> obj = geojson.Point((-3.68,40.41,25.14,10.34))
>>> obj.is_valid
False
```

`errors` method provides collection of errors when validation GeoJSON objects.

```
>>> import geojson

>>> obj = geojson.Point((-3.68,40.41,25.14,10.34))
>>> obj.errors()
'a position must have exactly 2 or 3 values'
```

4.6 generate_random

`geojson.utils.generate_random` yields a geometry type with random data

```
>>> import geojson

>>> geojson.utils.generate_random("LineString")
{"coordinates": [...], "type": "LineString"}

>>> geojson.utils.generate_random("Polygon")
{"coordinates": [...], "type": "Polygon"}
```

CHAPTER 5

Development

To build this project, run `python setup.py build`. To run the unit tests, run `python -m pip install tox && tox`. To run the style checks, run `flake8` (install *flake8* if needed).

CHAPTER 6

Credits

- Sean Gillies <sgillies@frii.com>
- Matthew Russell <matt@sanoodi.com>
- Corey Farwell <coreyf@rwell.org>
- Blake Grotewold <hello@grotewold.me>
- Zsolt Ero <zsolt.ero@gmail.com>
- Sergey Romanov <xxsmotur@gmail.com>
- Ray Riga <ray@strongoutput.com>